

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Cordless rotary hammer drill 18,0 V

CHE 2-26 18.0-EC

Order number 478.482



Cordless rotary hammer drill 18,0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Powerful motor with 2.6 joules of impact energy and a high rate of removal
- + Drilling chuck can be removed without tools
- + Quick tool change: universal application, with SDS Plus drill chuck or 13 mm quick-release chuck
- + Accelerator switch with lock-on function
- + Electronic quick-acting brake
- + Rotation stop for chiselling
- + Function switch with four functions: drilling, hammer drilling, chiselling, chisel adjustment
- + Robust gearbox housing made of die-cast aluminium
- + Decoupled, ergonomic handle with rubberised grip surface. Vibrations are reduced by a sprung damper and additional vibration damping between the housing and handle
- + Non-rotating additional handle with depth stop
- + Integrated LED lamp with persistence function
- + Ideal for daily use for drilling and chiselling in concrete, brickwork, timber and metal
- + LED battery capacity display
- + FLEX battery system: suitable for FLEX 18,0 V/5,0 Ah battery packs. Delivery does not include battery and charger

Technical attributes

Battery voltage	18 V
Battery capacity	5,0 Ah
No load speed	0-980 rpm
Blows per minute	0-4350 bpm
Single impact energy (EPTA)	2,6 J
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in concrete	26 mm
Max. drill hole Ø in wood	30 mm
Tool fixture	SDS-plus
Chuck Ø	1,5 - 13 mm
Size (W x L x H)	360 x 85 x 230 mm
Weight without battery	3,18 kg

Standard equipment

1 chuck BF SDS-plus CHE2	468.835
1 handle	436.364
1 depth stop	417.769
1 carrying case L-BOXX® 238	414.093
1 case insert	488.356